

PRO5

Tri Proof LED Batten



Applications: Commercial, residential, educational facilities, industrial and warehouse, amenity areas, hospitals

PERFORMANCE SUMMARY

The Sunled PRO5 Series is ideal for flexible deployment in economical lighting structures. The PRO5 design is suitable for ceiling, pendant and trunking rail mounting.

PRO5 has been developed with durability in mind with a rugged shatter proof lamp cover and inside prisms for excellent edge stability. PRO5 Tri offers unique uniform light distribution that ensures a glare-free environment.

Construction

- Refined slimline appearance for everyday lighting needs
- High impact polyester housing and polycarbonate diffuser with IK10 impact rating
- Age resistant IP65 silicon gasket seals
- Cable entry knock out on both sides with quick release end caps
- Tamper resistant polycarbonate lens housing
- Glare free diffuser for uniform light distribution
- Standard fixture includes ceiling and suspended mounting kits

Electrical

- Series linkable plug and play connection capability factory fitted in 2/4/5ft cable lengths up to 10 units
- Emergency battery backup
- Optional behind lens motion sensor and daylight sensors smart control options
- 0-10V dimming
- AC100-277V
- Average rated life L70: >50,000H
- CRI RA80

PRODUCT CODE



Example PRO5 cat. 4L.40.5.5.SS.M

Model No	Length	Wattage (W)	Connectors	CCT (°K)	Mounting	Control
Pro5	2L - 2ft	20 - 20W/2,400 lms	2 - 2ft	3 - 3000	S - Surface	EM - Emergency Battery Backup
	3L - 3ft	30 - 30W/3,600 lms	4 - 4ft	4 - 4000	SS - Suspended	MS - Behind Lens Motion Sensor
	4L - 4ft	40 - 40W/4,800 lms	5 - 5ft	5 - 5000		RC - Remote Control
	5L - 5ft	60 - 60W/7,200 lms	0 - None	6 - 6000		0 - None



Specification	
Lumen Package	2,600 - 7,800
Wattage Range	20 - 60
Efficacy	130
Weight lbs (kg)	5.7 (2.6) - 9.2 (4.2)

PHOTOMETRICS




PR05



Tri Proof LED Batten

DIMENSIONS


2ft — 20W




3ft — 30W



4ft — 40W




5ft — 60W



OPTIONS



2/3/5ft
Linkage
Connectors



RC
Remote
Control



MS
Motion Sensor
Behind Lens

SENSOR RANGE

