

# SLATE

Full Cutoff Wallpack



**Applications:** Building perimeters, residential courtyards, exterior security, building facades, pathway and perimeter lighting

## PERFORMANCE SUMMARY

Whether you are trying to meet specification, code, or seeking a building mount solution with the right options, the Slate LED was designed to provide elegant wall-mounted lighting solutions for building perimeter applications

With clean square lines, it blends seamlessly into any architecture, meeting the everyday lighting needs of engineers and architects alike. The Slate comes in both in up or down distributions and 600 to 4,000 lumens packages

## Construction

- Durable extruded heavy duty die cast aluminium housing
- Surface finished with a proprietary Akzo Nobel treatment, withstanding harsh weather conditions without cracking or peeling

## Optical

- Available in T3 symmetric or T4 asymmetric distribution options for facade or area illumination applications
- Dark sky friendly with minimal uplight of less than 5% total lumen output illuminating above 900 (down only model)
- Tempered glass lens
- Long life aluminium LED COB with added corrosion resistance for enhancing protection against moisture and contaminants
- Delivered lighting output up to 4,000 median lumens
- Easy installation with threaded conduit holes on back of fixture

## Electrical

- Long life drivers up to L70/80,000 hours at 77°F
- Class 2 high efficiency LED driver, with an optional 1-10V dimming
- Wide range input voltage AC100-277V 0-10V dimmable

## Specification

Volts: AC100-240V  
 MacAdam Step: SDCM < 5  
 Average Rated Life: 60,000hrs  
 Dimming: 0-10V  
 CRI: > RA80  
 Environment Location: IP65  
 Ambient Temp: -4°F to 122°F

## PRODUCT CODE



Example Slate cat. 1.C06.1.T3.27.B.M

Model No	Beam Angle	Wattage (W)	Distribution	CCT (°K)	Housing Color	Accessories
Slate	1 - Up or Down	C06.1 - 6W x1/600lm x1	T3 - Type 3	27 - 2700	B - Black RAL9011 W - White RAL9016 G - Gray RAL7012 M - Mineral Bronze S - Silver RAL9006	EM - 8W/90min Emergency M - Marine resistance DIM - 0-10V dimming O - None
		C20.1 - 20W x1/2000lm x1	T4 - Type 4	30 - 3000		
	2 - Up and Down	C06.2 - 6W x2/600lm x2		40 - 4000		
		C20.2 - 20W x2/2000lm x2		60 - 6000		





## PHOTOMETRICS

### Type 3 (T3)



### Type 4 (T4)



## DIMENSIONS

Weight: (May vary with accessories)  
 6.6lbs (3.0kg)

