# **AUGUSTUS MOD/C**

Open Ended LED Urban Light











## PERFORMANCE SUMMARY

Made from a lightweight yet robust material, the Augustus series LED Urban Light merges classic and modern design elements together to create a stunning luminaire perfect for grand promenades, business districts, shopping malls and parks alike.

The Augustus series is supplied with a double layer of protective paint resistant to corrosion and UV rays

#### Construction

- Contemporary design blends harmoniously into urban environments
- Heavy duty injection die cast aluminium housing and cover
- UV stabilised polyester powdercoat finish for durability and corrosion resistance. Available in matt black (standard), bronze, or white finishes
- 5mm tempered glass lens

## **Optics**

- Optical control delivers 4 distributions in type II, III, IV, V
- Engineered individual lenses made of optical grade polycarbonate for maximum light efficiency
- Dark sky friendly with minimal uplight of less than 5% total lumen output illuminating above 900mm

#### **Electrical**

- Philips SPD (10kV) built in surge protection device
- Class 1 dimmable electronic driver with PF > 90%, THD <20%, 50.000hrs servicable life with <1% failure rate</li>
- LumiLEDs 3030 light engine mounted to a stainless steel heatsink ensuring optimal thermal management and long life

## **Specification**

Volts: AC120-277V PF: > 0.90 CRI: RA70 Average Rated Life: 50,000hrs Environment Location: IP65 Ambient Temp: -20°F to 113°F Mounting: Φ60/76mm

## **PRODUCT CODE**

Example Augustus Mod/C cat. 60.T3.35.PB.BL.PE

| Model No       | Wattage (W)           | Distribution | CCT (°K)  | Mounting         | Finish          | Control                                     |
|----------------|-----------------------|--------------|-----------|------------------|-----------------|---|
|                |                       |              |           |                  |                 |   |
| Augustus Mod/C | 30 - 30W/3,600 lms    | T2 - Type 2  | 3 - 3000  | PA - 60mm Pole   | BL - Matt Black | PE - Top Mount<br>Photoelectric<br>O - None |
|                | 60 - 60W/7,200 lms    | T3 - Type 3  | 35 - 3500 | PB - 76mm Pole   | BR - Bronze     |   |
|                | 90 - 90W/10,800lms    | T4 - Type 4  | 4 - 4000  | WB- Wall Bracket | W - White       |   |
|                | 150 - 150W/18,000 lms | T5 - Type 5  | 5 - 5000  |                  |                 |   |



## **DIMENSIONS**




# **AUGUSTUS MOD/C**


Open Ended LED Urban Light

# **PHOTOMETRICS**


## Type 2 (T2)



## **Type 3 (T3)**



# Type 4 (T4)



**Type 5 (T5)** 

