Round LED Highbay













Applications: Industrial and warehouse, factories, retail and grocery, shopping mall, supermarkets, exhibition centers

PERFORMANCE SUMMARY

The HiEye Series LED High Bay luminaire delivers up to 41,400 lumens with illumination performance to allow for replacement of 400W metal halide high-bay lighting and multi-lamp fluorescent high-bay fixtures.

The HiEye Series obsoletes the need to continue using energy-wasting and high maintenance fluorescent and HID high-bay fixtures.

Features

- On board field selectable, 4 way power control
- Exceptional operating efficiency of 138lm/W
- High output Philips LumiLED 2835 COB
- 4kV built in surge protection
- Die cast thick gauge aluminium alloy construction
- Surface finished with a proprietary electrostatic coating, withstanding harsh industrial conditions without cracking or peeling
- Available with both acrylic and aluminum reflector, for an array of commercial and industrial applications
- Delivered lighting output from 4,140 to 41,000 median lumens
- Integral screw on motion sensor option
- DLC Premium 5.0 qualified product

Specification

Volts: AC100-277/277-480V Average Rated Life: 70,000hrs

Dimming: 0-10V

Environment Location: IP65

PF: > 0.9 THD: < 20% CRI: RA80 Ambient temp: -40°F to 122°F Surge: 4kV line neutral


Impact Rating: IK10

PRODUCT CODE


Example HiEye 120 cat. 100.ACB.4.12.B.H.MD/EM



PHOTOMETRICS 90° (90)







| Model | Wattage | Accessories | CCT (°K) | Beam Angle | Finish | Mount | Control ¹ |
|-----------------------|--|-----------------------------|--|----------------------|------------------------|-----------------------|---|
| HiEye 120 100-277V | 100 - 30/50/80/100W 4140/6900/11040/13800lms | AL - Aluminium Reflector | 4 - 4000 5 - 5000 | 12 - 120° 9 - 90° | B - Black W - White | H - Hook YK - Yoke | EM - Emergency Battery Backup, 2000lm/90min |
| HiEye 400 277-480V | 150 - 50/80/100/150W | AC - Acrylic Reflector | 345 ³ - CCT Selectable 3/4/5/5700 | 3 - 30 | w winte | 0 - 0-Ring | |
| | 6900/11040/13800/20700lms | | | | | | R(n) ² - Remote Control |
| | 200 - 80/100/150/200W | ACB - Acrylic | | | | | |
| | 11040/13800/20700/27600lms | Reflector/Bottom | | | | | MD - Motion Sensor |
| | 230 - 100/150/200/230W 13800/20700/27600/31740lms | Cover | | | | | |
| | | WG - Wire Guard | | | | | 0 - None |
| | 300 - 150/200/230/300W 20700/27600/31740/41400lms | 0 - None | | | | | |

NOTES

¹R can only be selected together with MD that can be used for programming (at least one per job site) ²Denotes 'n' quantity required

3CCT selectable available in 150/230W



HIEYE

Round LED Highbay

MOUNTING



OR O-Ring



H Hook



YK Yoke

CONTROL Emergency Pack (EM)



Motion Sensor (MD)



REFLECTOR Acrylic (AC)



Acrylic/Bottom Cover (ACB)



Aluminium (AL)




Wireguard (WG)




HIEYERound LED Highbay

DIMENSIONS 300W




200/230W



100/150W









Motion Detector (MD)

*Remote Control Optional









Wall Mounted Detection Pattern (m)